



FDX XTREME

PREMIUM



TW Premium
Self-priming pump



TW 500 Premium

On request
hose reel kit



NEW
B&S
VANGUARD
ENGINES
(18 or 31 HP)



FOR MORE
INFORMATION



BOX DIMENSION (cm)	111 x 90 x 120
QUANTITY FOR PALLET	1
PALLET DIMENSION (cm)	111 x 90 x 120
N. MACHINES CONTAINER 20'	24
N. MACHINES CONTAINER 40' (40' HQ)	52



RPM
deceleration kit



Rear wheel
with brake

GENERAL FEATURES

- ø 300mm 4 wheels with foamed-acting pneumatic
- Engines: Honda GX 690 or B&S Vanguard (18 or 31 HP)
- Gearbox (with 1560 rpm pump)
- Electrical starting
- No engine-oil safety device (oil-alert)
- Hours meter (on models with HONDA engine)
- Automatic decelerator to reduce the number of revs in the bypass phase
- Stainless steel gradual pressure restoration valve with EASY START
- Thermostatic valve
- Big water filter at pump inlet, readily serviceable cartridge type

TECHNICAL FEATURES

CODE	MODELS	PUMP										
			bar	MPa	bar	MPa	l/h	HP	kW	kg	(L x W x H) cm	
9058 0025	FDX Xtreme 18/350 Vanguard B&S 18 HP	TW Premium	360	36	50÷350	5÷35	410÷1080	18,0	13,4	150	100 x 82 x 85	
9058 0001	FDX Xtreme 15/500 Honda GX690	TW Premium 500	520	52	100÷500	10÷50	440÷990	22,0	16,4	150	100 x 82 x 85	
9058 0002	FDX Xtreme 18/400 Honda GX690	TW Premium 500	415	41,5	50÷400	5÷40	380÷1080	22,0	16,4	150	100 x 82 x 85	
9058 0003	FDX Xtreme 21/350 Honda GX690	TW Premium	360	36	50÷350	5÷35	480÷1260	22,0	16,4	150	100 x 82 x 85	
9058 0004	FDX Xtreme 30/280 Honda GX690	TW Premium	280	28	50÷270	5÷27	770÷1800	22,0	16,4	150	100 x 82 x 85	
9058 0005	FDX Xtreme 36/230 Honda GX690	TW Premium	230	23	30÷220	3÷22	800÷2160	22,0	16,4	150	100 x 82 x 85	
9058 0006	FDX Xtreme 42/180 Honda GX690	TW Premium	180	18	30÷170	3÷17	1060÷2520	22,0	16,4	150	100 x 82 x 85	
9058 0015	FDX Xtreme 53/140 Honda GX690	TW Premium	150	15	30÷140	3÷14	1380÷3090	22,0	16,4	150	100 x 82 x 85	
9058 0024	FDX Xtreme 21/500 Vanguard B&S 31 HP	TW Premium 500	520	52	100÷500	10÷50	560÷1260	31,0	23,1	150	100 x 82 x 85	

STANDARD EQUIPMENT



GH 401 gun with Swivel (n.2 o-ring)

TECHNICAL FEATURES					COMPATIBLE MODELS								
l/min	IN	OUT	bar	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
30	M24x1,5 M	M24x1,5 F	400	2410 0256									



GH 501 stainless steel gun with quick couplers 600 bar

TECHNICAL FEATURES					COMPATIBLE MODELS								
l/min	IN	OUT	bar	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
60	M24x1,5M	M24x1,5F	700	2410 0220									



L50 straight Stainless Steel lance with ball quick coupler, without nozzles

TECHNICAL FEATURES				COMPATIBLE MODELS								
IN	OUT	mm	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M24x1,5 M	1/4" F NPT	1200	3301 1521									



Straight stainless steel lance, with adjustable handle

TECHNICAL FEATURES				COMPATIBLE MODELS								
IN	OUT	mm	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M24x1,5 M	1/4" F NPT	1220	3301 1401									



Flat stainless-steel spray nozzle max 350/500 bar (available in stainless steel/tungsten on request)

TECHNICAL FEATURES				COMPATIBLE MODELS								
IN	Ø	°	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
1/4" NPT M	043	15	3400 0717									
1/4" NPT M	020	15	3400 0675									
1/4" NPT M	028	15	3400 0709									
1/4" NPT M	040 ceramic	15	3400 0651									
1/4" NPT M	050	25	3400 0652									
1/4" NPT M	075	25	3400 0761									
1/4" NPT M	10	25	3400 0654									
1/4" NPT M	13	25	3400 0655									

STANDARD EQUIPMENT



Delivery hose kit with quick couplers

TECHNICAL FEATURES				COMPATIBLE MODELS								
IN	OUT	m	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M 24x1,5 F	M 24x1,5 F	10 - R2 3/8"	3301 1361									
M 24x1,5 F	M 24x1,5 F	20 - R2 3/8" 600 bar	3301 1226									
M 24x1,5 F	M 24x1,5 F	20 - R2 3/8" 400 bar	3301 1270									
M 24x1,5 F	M 24x1,5 F	20 - R2 1/2" 300 bar	3301 1268									



Self cleaning water filter

TECHNICAL FEATURES				COMPATIBLE MODELS								
IN	OUT	mesh	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
G 1" F	G 1" F	80	1002 0241									



Cartridge for water filter

TECHNICAL FEATURES				COMPATIBLE MODELS								
IN	OUT	mesh	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
-	-	80	1002 0242									

ACCESSORIES



Concentrated stainless-steel jet nozzle with ceramic insert (available in stainless steel/tungsten on request)

TECHNICAL FEATURES				COMPATIBLE MODELS								
IN	∅		CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
1/4" NPT M	030 ceramic	0	3400 0619									
1/4" NPT M	040 ceramic	0	3400 0620									
1/4" NPT M	050 ceramic	0	3400 0622									
1/4" NPT M	075	0	3400 0623									
1/4" NPT M	11	0	3400 0624									
1/4" NPT M	15	0	3400 0626									



Lance with rotating nozzle with quick couplers M24x1,5 (600 bar)

TECHNICAL FEATURES				COMPATIBLE MODELS								
IN	∅	bar	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M24x1,5 M	030 stainless steel	600	3301 1544									
M24x1,5 M	040 stainless steel	600	3301 1546									
M24x1,5 M	050 stainless steel	600	3301 1327									
M24x1,5 M	075 brass	400	3301 1548									
M24x1,5 M	11 brass	400	3301 1549									
M24x1,5 M	15 brass	400	3301 1550									



Stainless steel straight rotating nozzle lance with ball quick coupler

TECHNICAL FEATURES				COMPATIBLE MODELS								
IN	∅	bar	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M24x1,5 M	045	400	3301 1536									



Delivery hose kit 20 mt with quick couplers M24x1,5

TECHNICAL FEATURES				COMPATIBLE MODELS								
IN	OUT	m	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M 24x1,5 F	M 24x1,5 M	20 - R2 - 3/8" - 600 bar	3301 1255									
M 24x1,5 F	M 24x1,5 M	20 - R2 - 3/8" - 400 bar	3301 1440									
M 24x1,5 F	M 24x1,5 M	20 - R2 - 3/8" - 400 bar	3301 1271									
M 24x1,5 F	M 24x1,5 M	20 - R2 - 1/2" - 300 bar	3301 1269									



Kit raccordo per testina ugello rotante

TECHNICAL FEATURES				COMPATIBLE MODELS								
IN	OUT	CODE		9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
1/4 NPT-M	G 1/4 M	5027 0035										



Rotating nozzle head - G 1/4" F (a ricambio) (con inserti in tungsteno)

TECHNICAL FEATURES				COMPATIBLE MODELS								
IN	Ø	bar	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
G 1/4" F	030 inox	600	3217 0331									
G 1/4" F	040 inox	600	3217 0327									
G 1/4" F	050 inox	600	3217 0329									



Rotating nozzle head - G 1/4" F (a ricambio) (con inserti in ceramic)

TECHNICAL FEATURES				COMPATIBLE MODELS								
IN	Ø	bar	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
G 1/4" F	075 brass	400	3217 0325									
G 1/4" F	10 brass	400	3217 0277									
G 1/4" F	15 brass	400	3217 0286									



Sand/Soda blasting lance kit completa di testina, sonda regolabile e tubo gomma aspirazione. Con attacchi rapidi M24x1,5 (600 bar)

TECHNICAL FEATURES				COMPATIBLE MODELS								
IN	bar	Ø	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M24x1,5 M	500	030	3301 1333									
M24x1,5 M	500	030	3301 1450									
M24x1,5 M	500	040	ON REQUEST									
M24x1,5 M	500	050	3301 1334									
M24x1,5 M	500	080	3301 1335									
M24x1,5 M	500	090	3301 1336									



Kit Protective clothing kit

TECHNICAL FEATURES				COMPATIBLE MODELS								
Kit	bar	-	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
Grebiule	500	-	0608 0070									



Kit sonda spurgatubi 25 m con attacchi rapidi M24x1,5 (600 bar)

TECHNICAL FEATURES				COMPATIBLE MODELS								
IN	bar	l/min	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M24x1,5 M	350	16 ÷ 29	3045 0067									
M24x1,5 M	600	10 ÷ 15	3045 0050									
M24x1,5 M	600	16 ÷ 29	3045 0051									
M24x1,5 M	600	30 ÷ 42	3045 0052									



Foot valve

TECHNICAL FEATURES				COMPATIBLE MODELS								
IN	OUT	bar	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M 24x1,5 M	M 24x1,5 F	500	0608 0071									



Kit avvolgitubo con attacchi rapidi con tubo Blu anti-macchia

TECHNICAL FEATURES				COMPATIBLE MODELS								
Hose type	m	OUT	CODE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
R2 - 3/8" - 600 bar	20	M24x1,5F	7002 0336									
R2 - 1/2" - 300 bar	20	M24x1,5F	7002 0342									



FDX XTREME

PREMIUM



TW Premium
Pompa autoadescente

TW 500 Premium

Su richiesta kit avvolgitubo



NEW
B&S
VANGUARD
ENGINES
(18 or 31 HP)



PER MAGGIORI
INFORMAZIONI



DIMENSIONI IMBALLO (cm)	111 x 90 x 120
QUANTITÀ BANCALE	1
DIMENSIONI BANCALE (cm)	111 x 90 x 120
N. MACCHINE IN BOX DA 20'	24
N. MACCHINE IN BOX DA 40' (40' HQ)	52



Kit deceleratore di giri motore



Ruota posteriore dotata di freno

CARATTERISTICHE GENERALI

- 4 ruote schiumate ø300mm con effetto pneumatico
- Motori: Honda GX 690 oppure B&S Vanguard (18 o 31 HP)
- Riduttore di giri (con pompa a 1560 rpm)
- Avviamento elettrico
- Dispositivo di Sicurezza mancanza olio motore (oil-alert)
- Contatore (solo su modelli con motore HONDA)
- Deceleratore automatico per la riduzione del numero di giri in fase di by-pass
- Valvola a ripristino graduale della pressione in acciaio inox con EASY START
- Valvola termostatica
- Filtro acqua di grande dimensione in ingresso pompa a cartuccia ispezionabile
- Uso altamente professionale

CARATTERISTICHE TECNICHE

CODICE	MODELLI	POMPA	MAX		WORK		WORK		WORK		kg	(L x W x H) cm
			bar	MPa	bar	MPa	l/h	HP	kW			
9058 0025	FDX Xtreme 18/350 Vanguard B&S 18 HP	TW Premium	360	36	50÷350	5÷35	410÷1080	18,0	13,4	150	100 x 82 x 85	
9058 0001	FDX Xtreme 15/500 Honda GX690	TW Premium 500	520	52	100÷500	10÷50	440÷990	22,0	16,4	150	100 x 82 x 85	
9058 0002	FDX Xtreme 18/400 Honda GX690	TW Premium 500	415	41,5	50÷400	5÷40	380÷1080	22,0	16,4	150	100 x 82 x 85	
9058 0003	FDX Xtreme 21/350 Honda GX690	TW Premium	360	36	50÷350	5÷35	480÷1260	22,0	16,4	150	100 x 82 x 85	
9058 0004	FDX Xtreme 30/280 Honda GX690	TW Premium	280	28	50÷270	5÷27	770÷1800	22,0	16,4	150	100 x 82 x 85	
9058 0005	FDX Xtreme 36/230 Honda GX690	TW Premium	230	23	30÷220	3÷22	800÷2160	22,0	16,4	150	100 x 82 x 85	
9058 0006	FDX Xtreme 42/180 Honda GX690	TW Premium	180	18	30÷170	3÷17	1060÷2520	22,0	16,4	150	100 x 82 x 85	
9058 0015	FDX Xtreme 53/140 Honda GX690	TW Premium	150	15	30÷140	3÷14	1380÷3090	22,0	16,4	150	100 x 82 x 85	
9058 0024	FDX Xtreme 21/500 Vanguard B&S 31 HP	TW Premium 500	520	52	100÷500	10÷50	560÷1260	31,0	23,1	150	100 x 82 x 85	

DOTAZIONE STANDARD



Pistola GH 401 con Swivel (n.2 o-ring)

CARATTERISTICHE TECNICHE					MODELLI COMPATIBILI								
l/min	IN	OUT	bar	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
30	M24x1,5 M	M24x1,5 F	400	2410 0256									



Pistola GH 501 inox con attacchi rapidi 600 bar

CARATTERISTICHE TECNICHE					MODELLI COMPATIBILI								
l/min	IN	OUT	bar	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
60	M24x1,5M	M24x1,5F	700	2410 0220									



Lancia dritta L50 inox con attacco rapido a sfere, senza ugelli

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
IN	OUT	mm	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M24x1,5 M	1/4" F NPT	1200	3301 1521									



Lancia inox dritta, con impugnatura regolabile

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
IN	OUT	mm	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M24x1,5 M	1/4" F NPT	1220	3301 1401									



Ugello inox getto piatto max 350/500 bar (disponibile su richiesta in materiale inox/tungsteno)

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
IN	Ø	°	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
1/4" NPT M	043	15	3400 0717									
1/4" NPT M	020	15	3400 0675									
1/4" NPT M	028	15	3400 0709									
1/4" NPT M	040 ceramic	15	3400 0651									
1/4" NPT M	050	25	3400 0652									
1/4" NPT M	075	25	3400 0761									
1/4" NPT M	10	25	3400 0654									
1/4" NPT M	13	25	3400 0655									

DOTAZIONE STANDARD



Kit tubo mandata con attacchi rapidi

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
IN	OUT	m	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M 24x1,5 F	M 24x1,5 F	10 - R2 3/8"	3301 1361									
M 24x1,5 F	M 24x1,5 F	20 - R2 3/8" 600 bar	3301 1226									
M 24x1,5 F	M 24x1,5 F	20 - R2 3/8" 400 bar	3301 1270									
M 24x1,5 F	M 24x1,5 F	20 - R2 1/2" 300 bar	3301 1268									



Filtro acqua autopulente

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
IN	OUT	mesh	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
G 1" F	G 1" F	80	1002 0241									



Cartuccia per filtro acqua

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
IN	OUT	mesh	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
-	-	80	1002 0242									

ACCESSORI



Ugello inox getto concentrato con inserto in ceramica (disponibile su richiesta in materiale inox/tungsteno)

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
IN	Ø		CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
1/4" NPT M	030 ceramica	0	3400 0619									
1/4" NPT M	040 ceramica	0	3400 0620									
1/4" NPT M	050 ceramica	0	3400 0622									
1/4" NPT M	075	0	3400 0623									
1/4" NPT M	11	0	3400 0624									
1/4" NPT M	15	0	3400 0626									



Lancia con ugello rotante con attacchi rapidi M24x1,5 (600 bar)

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
IN	Ø	bar	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M24x1,5 M	030 inox	600	3301 1544									
M24x1,5 M	040 inox	600	3301 1546									
M24x1,5 M	050 inox	600	3301 1327									
M24x1,5 M	075 ottone	400	3301 1548									
M24x1,5 M	11 ottone	400	3301 1549									
M24x1,5 M	15 ottone	400	3301 1550									



Lancia diritta inox Ugello Rotante con attacco rapido a sfere

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
IN	Ø	bar	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M24x1,5 M	045	400	3301 1536									



Kit tubo mandata 20 mt con attacchi rapidi M24x1,5

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
IN	OUT	m	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M 24x1,5 F	M 24x1,5 M	20 - R2 - 3/8" - 600 bar	3301 1255									
M 24x1,5 F	M 24x1,5 M	20 - R2 - 3/8" - 400 bar	3301 1440									
M 24x1,5 F	M 24x1,5 M	20 - R2 - 3/8" - 400 bar	3301 1271									
M 24x1,5 F	M 24x1,5 M	20 - R2 - 1/2" - 300 bar	3301 1269									



Kit raccordo per testina ugello rotante

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
IN	OUT	CODICE		9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
1/4 NPT-M	G 1/4 M	5027 0035										



Testina ugello rotante - G 1/4" F (a ricambio)
(con inserti in tungsteno)

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
IN	Ø	bar	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
G 1/4" F	030 inox	600	3217 0331									
G 1/4" F	040 inox	600	3217 0327									
G 1/4" F	050 inox	600	3217 0329									



Testina ugello rotante - G 1/4" F (a ricambio)
(con inserti in ceramica)

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
IN	Ø	bar	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
G 1/4" F	075 ottone	400	3217 0325									
G 1/4" F	10 ottone	400	3217 0277									
G 1/4" F	15 ottone	400	3217 0286									



Kit lancia sabbicante/bicarbonato completa di testina,
sonda regolabile e tubo gomma aspirazione.
Con attacchi rapidi M24x1,5 (600 bar)

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
IN	bar	Ø	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M24x1,5 M	500	030	3301 1333									
M24x1,5 M	500	030	3301 1450									
M24x1,5 M	500	040	SU RICHIESTA									
M24x1,5 M	500	050	3301 1334									
M24x1,5 M	500	080	3301 1335									
M24x1,5 M	500	090	3301 1336									



Kit abbigliamento protettivo

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
Kit	bar	-	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
Grembiule	500	-	0608 0070									



Kit sonda spurgatubi 25 m
con attacchi rapidi M24x1,5 (600 bar)

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
IN	bar	l/min	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M24x1,5 M	350	16 ÷ 29	3045 0067									
M24x1,5 M	600	10 ÷ 15	3045 0050									
M24x1,5 M	600	16 ÷ 29	3045 0051									
M24x1,5 M	600	30 ÷ 42	3045 0052									



Valvola a pedale

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
IN	OUT	bar	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
M 24x1,5 M	M 24x1,5 F	500	0608 0071									



Kit avvolgitubo con attacchi rapidi con
tubo Blu anti-macchia

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI								
Tipo tubo	m	OUT	CODICE	9058 0025	9058 0001	9058 0002	9058 0003	9058 0004	9058 0005	9058 0006	9058 0015	9058 0024
R2 - 3/8" - 600 bar	20	M24x1,5F	7002 0336									
R2 - 1/2" - 300 bar	20	M24x1,5F	7002 0342									